



FOXAIR SERIES MOBILE HVAC

FOXAIR MAX LP

47,000 BTU

The FoxCart's FoxAir Max LP is a portable HVAC unit capable of delivering 47,000 BTU of refrigerated air for pre-cooling or maintenance operations, with a minimum ambient temperature of 35°F (1.67°C). With an additional 15 kW 'Heater' option, the FoxAir Max LP can create that comfortable climate year round.

STANDARD FEATURES

SEALED REFRIGERANT SYSTEM FOR UNMATCHED RELIABILITY AND PERFORMANCE
1570 CFM AIR MOVEMENT SYSTEM
20" x 25" x 2" AIR FILTER
QUICK-CONNECT COLLAR FOR QUICK AND EASY CONNECTION OF AIR DELIVERY HOSE
FOXAIR MAX LP IS MOUNTED ON A LOW PROFILE TROLLEY
INTEGRAL 21 GALLON VU-THRU CONDENSATION STORAGE TANK WITH DRAIN VALVE

OPTIONS AVAILABLE

15kW HEATER
AIR DELIVERY HOSE (12" LAY FLAT DUCT - 25 FOOT)
15 OR 25 FOOT (SPECIFY)
50 FOOT (REQUIRES EXTENSION COUPLING)
DRAIN HOSE KIT - 50 OR 100 FOOT (SPECIFY)
INTEGRAL FREEZE PROTECTION SWITCH PREVENTS CONDENSER COIL FREEZE-UP
50, 100, OR 150 FOOT INPUT POWER CABLE (PIGTAIL - SPECIFY)
CONVENIENCE OUTLET - 120 VAC (SPECIFY VOLTAGE)

INPUT

VOLTAGE RANGE	208 - 230 VRMS, 1Ø OR 3Ø 430 - 480, 3Ø 540 - 575, 3Ø 2 WIRE, PLUS SAFETY GROUND
FREQUENCY	60Hz ± 10%
SAFETY DISCONNECT	CIRCUIT BREAKER ON / OFF

INDICATORS

MIN AMBIENT TEMP	35°F
------------------	------

OPERATING CONDITIONS

MODES	COOL OR FAN ONLY
-------	------------------

CAPACITY RATINGS (OUTPUT)

COOLING BTU / TONS	47,000 / 4.00
HEATING (OPTIONAL)	15 kW
AIRFLOW	1570 CFM
ENERGY EFFICIENCY RATINGS	SEER - 14 EER - 11.5

ENVIRONMENTAL

MOISTURE PROTECTION	IP24
AIR FILTER	20" x 25" x 2" (QTY 2)
SOUND LEVEL	78 dBA

This product was manufactured in a plant whose quality management system is registered to ISO 9001:2015.

Unitron Power Systems • 10925 Miller Rd • Dallas, TX 75238
Sales: +1-800-527-1279 • Service: +1-214-343-7597 • Fax: +1-214-341-2099
info@UnitronLP.com • www.UnitronLP.com



FOXAIR- 60

WEIGHT (WEIGHT VARIES WITH OPTIONS) 885LBS (2,248KG)

